




Flow rate [l/min]



58123

Shower set with water outlet, 1,50 m flexible hose and antilimestone handshower

TECHNICAL FEATURES

- Presence of water supply connections: yes
- Power supply connections: G1/2" .
- Height: 264 mm •
- Width: 65 mm
- Depth: 84 mm .
- Handshower presence: Handshower included .
- Handshower type: Single-jet .
- . Handshower size: 32 mm
- Handshower jet type: RAINFALL •
- Handshower support type: Fixed
- Handshower hose presence: yes .
- Handshower hose length: 1.500 mm .
- Hose material: PVC .
- Flow rate: 9 l/min •

43,5 0.0 14.5 29.0 58.0 72.5 87.0 101,5 1 = Flow rate 14.0 3.7 13,0 3,2 12,0 11,0 2,6 10,0 9,0 GPMI 8.0 2.1 7.0 rate 6,0 1.6 5,0 Flow 4,0 1.1 3.0 0,5 2.0 1.0 0,0 0,0 1.0 2,0 3.0 4,0 6.0 7.0 5,0 Pressure [bar] Flow rate is referred to mixed water temperature of 38°C MOP (Maximum Operating Pressure): 5 bar

Pressure [PSI]

CERTIFICATIONS

- BELGAQUA, WRAS recognized
- The main components in contact with drinking water comply with ACS requirements, UBA list, KTW BWGL Production managed by a certified quality System compliant with ISO 9001:2015 For additionals approval contact Gessi S.P.A.

TECHNICAL PRESCRIPTION

- Working maximum pressure value 72.5 PSI in case of higher pressure, to use a pressure reducer. .
- Working pressure for an optimal installation: 43.5 PSI.
- Supply the product with mains water with a maximum temperature of 70 °C and for short periods of use. .
- In order to guarantee a long duration of the product and its total functionality install filter.

Product, measurements and specifications shown are subject to change without notice. Please refer to the current price list for further information. Gessi S.p.A. Parco Gessi, 13037 Serravalle Sesia (vercelli) Italy - Tel. +39 0163 454111- www.gessi.com - lead@gessi.it



- Test watertight and cleaning of the pipes before installing the tap.
- In any case please refer to the instruction manual and warranty provided with the product.

INDICATIONS FOR CLEANING

Clean only with a new microfiber cloth and soapy water and properly dry the item. Detergents, solvents, chemical agents, abrasive sponges, wire, wool, alcohol, etc. should not be used as these could irreparably damage product surfaces compromising its aesthetics and brightness.

ACCESSORIES AND FITTINGS

For additional matching bathroom accessories and fittings available, see official Gessi price list.

FINISHES CHARACTERISTICS

CHROME	The galvanic process is the basis of almost all Gessi finishes. The first production step consist in covering component with several layers of coating by electrochemical reactions. It makes durable finishes, virtually impervious to wear or scratches. Chrome has high resistance to corrosion and is easy to clean.
STAINLESS STEEL	Not many materials can praise a resistant similar to the stainless steel, that never, in every environmental condition, loose the proper shining, perfect elegance, the rich color, asking also a really minimum maintenance. Recyclable 100%, steel can be regenerated and reused forever, permitting to reduce the consumption of natural resource.
PVD COLORS	PVD are innovative finishes that allow best performances and technical qualities, characterized by unique mechanical resistance and exceptional brightness, that are made by letting vapours of metallic alloys deposit on chromed component. This process makes it possible to achieve excellent resistance to corrosion and abrasion. In addition, the technology allow for a great variety of colors according to the metal that are used.
LAQUERED	Laquered finishes, with their peculiar aesthetic performance, are made by covering the product with various layers of different kind of lacquer. For example, in order to obtain the aged look the process start with sandblasted component, that is firstly lacquered in gold and then in black or brown, then highly specialized artisans manually brush the surface, bringing back to light the golden tones.

For additionals finishes contact Gessi S.P.A